

Medium Voltage Temperature Sensors

OSENSA Innovations offers onsite support, commissioning, and training for all of its products. For immediate assistance with any technical issue, please contact support@osensa.com or call 1-888-732-0016.

OSENSA Innovations stands behind its products and services. All fiber optic temperature probes and signal conditioners ship with a full one year repair or replacement warranty. You may also purchase an extended five year warranty. Some conditions apply.

OSENSA offers cost-effective design and consulting services at discounted rates for high-volume OEM customers. Let the engineering team at OSENSA Innovations help you rapidly develop custom probes for your power monitoring application. OSENSA's team has many years of experience designing fiber optic temperature probes for various industrial environments.


For more information on any of our products or services please visit our website: www.osensa.com or email: info@osensa.com.




Reliable Direct Contact Temperature Sensing

OSENSA's medium voltage fiber optic temperature sensors install on switchgear contacts, bus bars, cast resin transformer, motor, and generator windings to provide reliable 24/7 thermal monitoring with noise-free performance. The probes are constructed from durable, high dielectric strength materials and have been tested to safely operate on equipment rated up to 38 kV (3 phase). They install quickly and can be ordered with optional probe-tip attachments suitable for various applications.


Probe Specifications



PRB-GB3-02M-ST-L-TP1




PRB-PF1-02M-ST-L-TP2



| Model # | Maximum Rating | Sensing Range | Accuracy | Jacket | Bend Radius |
|------------------|----------------|---------------|----------|--------|-------------|
| PRB-GB3-02M-ST-L | 38 kV, 3 phase | -40 to +200°C | ±1.0°C | FEP | 8 mm |
| PRB-PF1-02M-ST-L | 38 kV, 3 phase | -40 to +120°C | ±1.0°C | Nylon | 15 mm |

CONNECTOR RING MOUNTING OPTIONS

ACC-CONN RING-0.375IN ACC-CONN RING-0.25IN ACC-CONN RING-0.50IN



- Compatible with OSENSA's FTX-301-PWR+, FTX-302-PWR+, FTX-602-PWR+, HTX-100-PWR, and FTX- 300-LUX+ fiber optic signal conditioners.
- Probe lengths can be specified from 0.5m to 10m.
- For longer distances add extension cable EXT-PF1-02M-ST-ST, in lengths from 2m to 20m.

Toll Free: 1-888-732-0016 International: 1-604-259-7177

Email: info@osensa.com

Specifications subject to change without notice.

DMK-0004A-12 ECO 1207