

PRB-220 Fiber Optic Temperature Probe

TECHNICAL SUBBORT

OSENSA Innovations offers onsite support, commissioning, and training for all of its products. For immediate assistance with any technical issue, please contact <u>support@osensa.com</u> or call 1-888-732-0016.

WARRANTY INFORMATION

OSENSA Innovations stands behind its products and services. All fiber optic temperature probes and signal conditioners ship with a full one year repair or replacement warranty. You may also purchase an extended five year warranty. Some conditions apply.

CUSTOM OEM SOLUTIONS

OSENSA offers cost-effective design and consulting services at discounted rates for high-volume OEM customers. Let the engineering team at OSENSA Innovations help you rapidly develop custom probes for your research application. OSENSA's team has many years of experience designing fiber optic temperature probes for various laboratory environments.

FURTHER INFORMATION

For more information on any of our products or services please visit our website: www.osensa.com or email: info@osensa.com.




MRI & Catheter Temperature Sensing

Non-magnetic, Non-Conducting, Optical Fiber Probes with Exceptional Precision

OSENSA's fast response PRB-220 catheter temperature probes provide accurate and reliable temperature sensing for a variety of life sciences, microwave and laboratory research applications requiring immunity to high intensity electro-magnetic fields and RF energy. These probes are constructed with high quality glass optical fiber and can handle temperatures up to 100°C while providing extremely fast response times. The polyimide tip is available in custom lengths.

Product Specifications

PRB-220-02M-STM-500-MRI



System Specifications	PRB-220-02M-STM-500-MRI
Calibrated Accuracy (10°C to 60°C)	± 0.10°C
Stability (15min)	± 0.02°C
Noise (1 second averaging)	± 0.02°C
Measurement Range	-40°C to 100°C
Immersion Response Time Constant	0.25s
Tip Diameter	260µm
Minimum Bend Radius	15mm
Probe Materials	PVC & Polyimide

Notes:

 Compatible with OSENSA's FTX-300-LUX+ series and FTX-020-OEM fiber optic signal conditioners.

Email: info@osensa.com

- 2. Probe lengths can be specified from 0.5m to 10m.
- 3. For longer distances add extension cable EXT-200-10M-STM-STM, in lengths from 2m to 50m.